

Module DALI 8 rail DIN

D-8DALI

Description

DIN rail unit for digital addressable lighting control (DALI). It can individually address up to 8 DALI drivers.

Functionalities

- Brightness regulation with automatic memory;
- Programmable timer switching;
- Power off after programmable delay;
- Scenarios with brightness memorization;
- Up to 24 buttons can be associated.

Application

Housing, Hotels, Offices, Factories.

Accessories

None.

Certifications

- EN 60669-2-1
- Low voltage directive 2014/35/EU
- EMC directive 2014/30/EU

Protections

The power supply to this unit must be protected by a 6A circuit breaker.

It is recommended to install a dedicated circuit breaker for each D-8DALI installed in the system.

Notes

The D-8DALI controller does not power the DALI drivers. The maximum length of the cable used for the DALI BUS, must not exceed 300m, with a section of 1.5mmØ



Assembly

DIN rail mounting, 2 space modules.

Connections

- L: Phase x 1 for 1.5 mm wire Ø
- N: Neutral x 1 for 1.5 mm wire Ø
- B: Bus x 1 for 1.5 mm wire Ø
- DA- : Out DALI - x 1 for 1.5 mm wire Ø
- DA+ : Out DALI + x 1 for 1.5 mm wire Ø

Electrical Characteristics

Power supply: 230 V 50 Hz

Maximum consumption: 0.5 W

Out: DALI

Warranty


The warranty is 5 years. Keep the invoice preserved for this purpose. Warranty is void if the product shows

- changes to the labels surrounding the product;
- electrical damage caused by misuse;
- surface damage such as scratches, cuts and tears.

Module DALI 8 rail DIN

D-8DALI

Dimensions



Wiring diagram

